




SBL 260-12i



Nominal Voltage	12 V
Nominal capacity	276 Ah @ C20 to 1,75 V/cell
	260 Ah @ C10 to 1,80 V/cell
Technology	AGM (Absorbent Glass Mat)
	VRLA (Valve Regulated Lead Acid)
Weight	~ 72 kg
Design life time	12 years (standby use)
	Long Life acc. Eurobat
Internal resistance	~ 2,6 mΩ (full charged)

Operating temperature range	Discharge -20°C ~ +60°C
	Charge 0°C ~ +50°C
	Storage -20°C ~ +60°C
Max. discharge current	2600 A (5 sec)
Short circuit current	4810 A
Max. charging current	78 A
Charging voltage	Standby use 13,6 ~ 13,8 VDC
	Cycle use 14,6 ~ 14,8 VDC
Self discharge	Monthly is less than 3% at 25°C
Container material	ABS UL94HB (optional UL94-V0)



Length	521 ±2 mm
Width	268 ±2 mm
Height	220 ±2 mm
Total height	225 ±2 mm
Internal thread M8 (breaking torque 10-12 Nm)	


CONSTANT CURRENT DISCHARGE CHARACTERISTICS (A at 25°C)

Napięcie/Czas	15 MIN	30 MIN	60 MIN	2 H	3 H	4 H	5 H	8 H	10 H	20 H
1.60 V	445,9	281,9	158,9	94,6	73,3	57,60	49,10	33,00	27,40	14,30
1.65 V	426,3	270,6	153,4	91,6	71,1	56,10	47,80	32,60	27,10	14,10
1.70 V	399,3	258,7	148,4	88,6	69,1	54,60	46,50	32,10	26,70	13,90
1.75 V	371,6	247,2	143,0	85,5	67,1	53,20	45,40	31,60	26,30	13,80
1.80 V	343,1	236,3	137,5	82,4	65,0	51,60	44,20	31,10	26,00	13,60
1.85 V	284,7	203,5	123,3	75,5	60,1	48,00	41,20	29,20	24,50	13,00


CONSTANT POWER DISCHARGE CHARACTERISTICS (W/cell at 25°C)

Napięcie/Czas	15 MIN	30 MIN	60 MIN	2 H	3 H	4 H	5 H	8 H	10 H	20 H
1.60 V	779,5	512,0	298,5	179,40	140,10	110,70	94,60	64,40	53,90	28,20
1.65 V	756,3	496,7	289,9	174,50	136,30	108,10	92,40	63,80	53,30	27,80
1.70 V	718,9	479,5	282,3	169,70	133,20	105,50	90,40	63,00	52,60	27,50
1.75 V	678,8	463,0	273,6	164,50	129,80	103,20	88,40	62,20	52,00	27,20
1.80 V	635,6	447,0	264,7	159,40	126,30	100,60	86,40	61,30	51,40	27,00
1.85 V	534,9	388,8	238,8	146,90	117,20	93,90	80,80	57,70	48,40	25,70


EFFECT OF TEMPERATURE ON LONG TERM LIFE




CYCLE LIFE IN RELATION TO DEPTH OF DISCHARGE




DISCHARGE CHARACTERISTICS CURVE



CHARGE CHARACTERISTIC CURVE FOR CYCLE USE



RELATIONSHIP BETWEEN CHARGING VOLTAGE AND TEMPERATURE





STORAGE CHARACTERISTICS



Standards met:

PN-EN 60896-21:2007 • PN-EN 60896-22:2007 • PN-EN 61056-1:2013 • PN-EN 61056-2:2013 • PN-E-83016:1999

Batteries manufactured in compliance with: ISO 9001 • ISO 14001



All data contained in this document, are subject to change. Wamtechnik Sp. z o.o. reserves the right to change them without prior notice.

Wamtechnik Sp. z o.o. ul. Techniczna 2 bud. H 05-500 Piaseczno
Tel. +48 22 701 26 00, office@wamtechnik.pl, www.wamtechnik.pl